


ACLED/0A/01/XX-XX/W/TF25

Cod. 029468 ACLED/0A/01/41-WH/W/TF25
 Cod. 029809 ACLED/0A/01/42-WW/W/TF25



Selezioni disponibili XX-XX
 Available selections XX-XX
 41-WH, 42-WW, 40-NW
 43-GR, 44-BL, 45-RE, 46-YE

| | | 41-WH Bianco Freddo 41-WH Cool White | 42-WW Bianco Caldo 42-WW Warm White | 40-NW Bianco Naturale 40-NW Natural White | 43-GR Verde - Green su richiesta - on demand | 44-BL Blu - Blue su richiesta - on demand | 45-RE Rosso - Red su richiesta - on demand | 46-YE Giallo Ambra Yellow Amber su richiesta - on demand |
|---|-----|---|--|--|---|--|---|--|
| Corrente nominale Rated current | mA | 350 | 350 | 350 | 350 | 350 | 350 | 350 |
| Tensione massima Max voltage | V | 4 | 4 | 4 | 4 | 4 | 3 | 3 |
| Potenza massima Max power | W | 1,4 | 1,4 | 1,4 | 1,4 | 1,4 | 1,23 | 1,23 |
| Flusso luminoso tipico Typical luminous flux | lm | 90 | 70 | 90 | 50 | 14 | 30 | 23,5 |
| Temperatura di colore / lunghezza d'onda Temperature colour / wavelength | K | 6000 | 3100 | 4000 | | | | |
| | nm | | | | 530 | 470 | 627 | 590 |
| Apertura angolare Viewing angle | °W | 60 | 60 | 60 | 60 | 60 | 60 | 60 |
| Peso unitario Weight | g | 10 | 10 | 10 | 10 | 10 | 10 | 10 |
| Imballo Packaging | pcs | 10 | 10 | 10 | 10 | 10 | 10 | 10 |

LUX diagramma / diagram
 Bianco / Cool white (41 - WH)

W
